

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCT

WELTORGANISATION FÜR
Internationales BüroINTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE
INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)

(51) Internationale Patentklassifikation 5 : G01N 33/543, 33/551, 33/547 G01N 21/55, 27/00	A1	(11) Internationale Veröffentlichungsnummer: WO 92/10757 (43) Internationales Veröffentlichungsdatum: 25. Juni 1992 (25.06.92) EPA 5,156,15
(21) Internationales Aktenzeichen: PCT/EP91/02393 (22) Internationales Anmeldedatum: 12. Dezember 1991 (12.12.91) (30) Prioritätsdatum: P 40 39 577.0 12. Dezember 1990 (12.12.90) DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): BOEHR RINGER MANNHEIM GMBH (DE/DE); Sandhofer Straße 112-132, D-6800 Mannheim (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): KNOLL Wolfgang (DE/ DE); Eisa-Brandström-Straße 18d, D-6500 Mainz (DE); SCHMITT, Franz-Josef (DE/DE); Matthiasstraße 19, D- 5501 Leiwen (DE); KLEIN, Christian (DE/DE); Blüter- straße 16, D-8120 Weilheim (DE).	(74) Anwälte: WEICKMANN, H. usw.; Kopernikusstrasse 9. D-8000 München 80 (DE). (81) Bestimmungsstaaten: AT (europäisches Patent), BE (euro- päisches Patent), CH (europäisches Patent), DE (euro- päisches Patent), DK (europäisches Patent), ES (euro- päisches Patent), FR (europäisches Patent), GB (euro- päisches Patent), GR (europäisches Patent), IT (europäi- sches Patent), JP, LU (europäisches Patent), MC (euro- päisches Patent), NL (europäisches Patent), SE (europäi- sches Patent), US. Veröffentlicht Mit internationalem Recherchenbericht	

(54) Title: UNIVERSAL BINDING FILM

(56) Bezeichnung: UNIVERSALBINDEFILM

(57) Abstract

A binding matrix contains a substrate upon which are adsorbed by means of anchoring groups solid phase reactants capable of binding at least one free reaction partner. The solid-phase reactant forms a diluted and essentially laterally homogeneous binding layer on the surface of the substrate. In addition, according to an assaying process for an analyte in an assay solution, a solid-phase reactant that forms a component of the disclosed binding matrix is used. The specific binding reaction is preferably determined by optical reflection techniques.

(57) Zusammenfassung

Die Erfindung betrifft eine Bindematrix, enthaltend ein Trägermaterial und einen daran über Ankergruppen adsorbierten Festphasen-Reaktanden, der mit mindestens einem freien Reaktionspartner bindesfähig ist, worin der Festphasen-Reaktand eine verdünnte und im wesentlichen lateral homogene Binde-schicht auf der Oberfläche des Trägermaterials bildet. Weiterhin wird ein Verfahren zur Bestimmung eines Analyten in einer Probelösung beansprucht, worin man einen Festphasen-Reaktanden verwendet, der Bestandteil einer erfindungsgemäßen Bindematrix ist. Dabei wird die spezifische Bindungsreaktion vorzugsweise durch reflexionsoptische Techniken bestimmt.

W. Klein
 B. Klein

BEST AVAILABLE COPY

02 - 1 - 33

Translation of Claims of International Patent

Number
WO 92/10757

Issued: June 25 1992

translated by:

Jost Vielmetter

Jost Vielmetter
10/17/96

WO 92/10757

-41-

PCT/EP91/02393

Claims

1. A binding matrix containing a carrier material coupled to a solid-phase reactant via anchoring groups which can couple with at least one reaction partner, wherein the solid-phase reactant forms a dissolved and basically laterally homogenous binding layer on the surface of the carrier material.
2. Binding matrix according to Claim 1, wherein the occupation of the solid-phase reactant on the surface of the carrier material ranges from 0.1% to 90% of the maximal occupation.
3. Binding matrix according to Claim 2, wherein the occupation of the solid-phase reactant on the surface of the carrier material ranges from 0.5% to 70% of the maximal occupation.
4. Binding matrix according to Claim 3, wherein the occupation of the solid-phase reactant on the surface of the carrier material ranges from 1% to 40% of the maximal occupation.
5. Binding matrix according to Claims 1 through 4, wherein the carrier material employs a metal-, metal oxide-, or glass-surface.

WO 92/10757

-42-

PCT/EP91/02393

6. Binding matrix according to Claim 5, wherein the carrier material employs a gold-, silver-, or palladium-surface and wherein the anchor group is a thiol-, disulfide-, or a phosphine-group.
7. Binding matrix according to Claims 1 through 6, wherein the anchor group is coupled to the solid-phase reactant via a flexible spacer molecule.
8. Binding matrix according to Claim 6, wherein the flexible spacer molecule contains at least one alkyl group with the formula $(CH)_n$ where n equals an integer number between 1 and 30.
9. Binding matrix according to Claims 7 or 8, wherein the spacer molecule is coupled to two or more solid phase reactants.
10. Binding matrix according to Claim 9, wherein the spacer molecule is a cystamin.
11. Binding matrix according to Claims 7 or 8, wherein a hydrophilic linker group is inserted between the spacer molecule and the solid phase reactant.
12. Binding matrix according to Claim 11, wherein the hydrophilic linker group contains one or more oxyethylene groups.

WO 92/10757

-43-

PCT/EP91/02393

13. Binding matrix according to Claim 12, wherein the hydrophilic linker group consists of an amine or hydroxyl-terminated polyethylene oxide.
14. Binding matrix according to Claim 13, wherein the hydrophilic linker group consists of a 1,8-diamino-3,6-dioxaoctane.
15. Binding matrix according to Claim 12, wherein besides the spacer molecules coupled to the solid-phase reactant other spacer molecules are present which contain anchoring groups that are not coupled to the solid phase reactant.
16. Binding matrix according to any of the previous Claims, wherein the solid phase reactant is an antigen or hapten able to bind to an antibody.
17. Binding matrix according to Claims 1 through 15, wherein the solid phase reactant is biotin.
18. Binding matrix according to Claims 7 or 8, wherein the solid phase reactant consists of an inner and an outer component where the outer component is capable of binding at least one free reaction partner.

WO 92/10757

-44-

PCT/EP91/02393

19. Binding matrix according to Claim 18, wherein the inner component of the solid phase reactant constitutes a non diluted layer on the surface of the carrier material and wherein the outer component is coupled to the inner component by affinity coupling.
20. Binding matrix according to Claim 19, wherein the inner component is biotin and the outer component is streptavidin.
21. A method to determine an analyte in a test sample solution via a specific binding reaction between at least two bioaffinity reactants one of which is coupled to the solid-phase and where the other reaction partners are free, wherein a solid-phase reactant is used which is part of a binding matrix according to any one of Claims 1 through 20.
22. A method according to Claim 21, wherein the specific binding reaction is determined optically, electronically, through the heat radiation, or the molecular masses.
23. A method according to Claim 21, wherein the specific binding reaction is determined by reflection-optical techniques.
24. A method according to Claim 23, wherein the specific binding reaction is determined by plasmon-spectroscopy.

WO 92/10757

-45-

PCT/EP91/02393

25. A method according to Claim 21, wherein the specific binding reaction is determined potentiometrically or amperometrically.
26. A method according to Claim 23, wherein the specific binding reaction is determined through the electrical conductivity or change in capacitance.
27. A method to construct a binding matrix according to any of the Claim 1 through 20, wherein the carrier material is incubated with a reaction solution containing molecules which from a binding layer adsorbed to the carrier material.